## GA-400 is using solution-dyed polypropylene yarn which cannot be easily discolored. Suitable for middle-low traffic areas in the office.

Composition	surface	Polypropylene 100%		dyeing method	of yarn Solution Dyed
	base fabric	Nonwoven Polyester		backing	PVC and Glass Fiber
	size	500mm x 500mm		overall thickr	ness 6.0mm
Specification	pile height	3.0mm (loop pile)			
	gauge	1/10	stitch	14.0	yarn weight (oz/sq.yd) 16.5

Packing	$20pcs/box = 5m^2/box$					
Net Weight	22.0kg/box					
Performance	Flame-retardant	Fire Defense Law in Japan Authorized No.E0970014				
	Antistatic	Less than 1.0kv (JIS L 1021-16, at 23 degrees centigrade, 25%RH)				
	Formaldehyde Radiation	F <sup>®</sup> ☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No. J04-30063				
Way of Installation	Quarter Turn					
Recommended Adhesive from TOLI	TOLL 500 04 00mont	(up assisted association)	for steel or plastic sub-floor	40 to 60 gram/m <sup>2</sup>		
	TOLI ECO GA Cement	(required quantity) -	for mortar and wood sub-floor	60 to 100 gram/m <sup>2</sup>		
Notes on Installation	Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.					
Others	Please note that the product has the indigenous odor from its materials.					

MADE IN JAPAN











GA-4003.					
Plain Color from GA-400	Matching Stripe Color from GA-400S				
GA4001 · GA4003	GA4401S (page 64)				
GA4017 · GA4020	GA4403S (page 64)				
GA4004 · GA4005	GA4405S (page 64)				
GA4016 · GA4019	GA4408S (page 64)				
GA4004 · GA4018	GA4409S (page 64)				
GA4009 · GA4028	GA4412S (page 64)				
GA4004 · GA4010	GA4413S (page 64)				
GA4017 · GA4023	GA4454S (page 65)				
GA4020 · GA4030	GA4456S (page 65)				
GA4003 · GA4004	GA4457S (page 65)				
GA4032 · GA4033	GA4458S (page 65)				
GA4005 · GA4035	GA4481S (page 65)				
GA4019 · GA4035	GA4482S (page 65)				
GA4032 · GA4035	GA4483S (page 65)				
GA4004 · GA4031	GA4484S (page 65)				