





FLOORLEUM MARBLE TOLI FLOORLEUM is the 40 years long-established vinyl sheet for multipurpose.

| Specification | overall thickness | 2.0mm / 2.5mm | width x length | 1820mm x 9m |
|---|--|--|----------------|-------------|
| JIS Registered No. | No. GB0506143 / No. GB0610001 (JIS A 5705 Vinyl Sheet Flooring) | | | |
| Packing | 9m/roll | | | |
| Net Weight | (2.0mm) 56.0kg/roll, (2.5mm) 73.0kg/roll | | | |
| Performance | Wear Resistance | (EN649) Group T | | |
| Recommended Adhesive from TOLI | dried mortar and concrete | Eco Royal Cement, Eco AR600 | | |
| | humid mortar and concrete | Epo Gray ST, US Cement, US Cement (less-smelly), US200 | | |
| | TOLI UNDERLAY SHEET | US Cement, US Cement (less-smelly), US200 | | |
| Welding | Welding rod for heat-welding is available on a color-by-color basis. | | | |
| Notes on Installation | +Seams should be heat-welded. +When you install 2 different sheets, each edge should be jointed at the seam. (Do not cut in the middle of the sheet.) +For one week after installation, direct sunlight, sudden change of temperature due to air conditioning, and water washing should be avoided. +As the sub-floor material, the underlayment like TOLI UNDERLAY SHEET (page 286) is also workable. Apply the same adhesive for both upside and downside of the underlayment. | | | |
| Recommended Maintenance Wax from TOLI | New FB Wax, U Wax, T Wax (Non-shiny & Antibacterial) | | | |
| Custom Order | Antibacterial spec. (ANTIBACTERIAL FLOORLEUM MARBLE) is also available. Please see the page 317. | | | |
| Others | ◆The dirt and stains will be more visible on the floor covering with lighter plain colors, compared to dark colors. Also they are more likely to stick with the deep-embossed surface than the flat surface. ◆Please be aware that some rubber casters might cause color-contamination. ◆Please note that the product has the indigenous odor from its materials. | | | |

MADE IN JAPAN











FLOORLEUM MARBLE



category: vinyl sheet

