



SOKOITARI INSPIRATION SOKOITARI's third generation that features the image of the ground and the following wind. The combination of "wavy base" pattern and "fair wind" pattern can create unprecedentedly elegant floor images.

Composition	surface	BCF	Nylon 100%	dyeing method	of yarn Piece Dyed	
	base fabric	Nonwo	ven Polyester	backing	PVC and Glass Fiber	
Specification	size	500m	m x 500mm	overall thickn	ess 7.5mm	
	pile height	H 5.0mm / L 3.0mm (textured loop pile)				
	gauge	1/12	stitch	12.5	yarn weight (oz/sq.yd) 24.8	

Packing	$16pcs/box = 4m^2/box$						
Net Weight	21.0kg/box						
Performance	Critical Radiant Flux	(ASTM E648)) Class 1 Average CRF 0.45/cm² or higher				
	Smoke Density (flaming)	(ASTM E662)	Less than 450				
	Flame-retardant Fire Defense Law in Japan Authorized No.E0070165						
	Antistatic	Less than 1.0kv (JIS L 1021-16, at 23 degrees centigrade, 25%RH)					
	Stain-resistant Stain Release						
	Formaldehyde Radiation	F [™] ☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No. J07-30442					
Way of Installation	↑ ↑ ↑ Monolithic or → ↑ Quarter Turn						
Recommended Adhesive from TOLI	TOLL 500 CA Comont	(va avviva d avva natite	for steel or plastic sub-floor	40 to 60 gram/m ²			
	TOLI ECO GA Cement	(required quantity	for mortar and wood sub-floor	60 to 100 gram/m ²			
Notes on Installation	◆Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly. ◆As SOKOITARI INSPIRATION is a solid-color imaged product, the shadows of joints are sometimes visible, which is not a manufacturing defect.						
Others	Please note that the product has the indigenous odor from its materials.						

MADE IN JAPAN





▲ GX8011/GX8012/GX8014/GX8021/GX8022/GX8024



GX8013

(PURPLE)





SOKOITARI INSPIRATION <GX-8000>

TOLI

category: carpet tile



▲ GX8011/GX8019/GX8021

