







MADE IN JAPAN

MV33

	Specification	overall thickness	2.0mm	size	303mm x 303mm
	JIS Registered No.	No. GB0307004 (JIS A 5705 Vinyl Tile Flooring)			
	Packing	50pcs/box = 4.59m			
	Net Weight	18.7kg/box			
	Recommended Adhesive from TOLI	dried mortar and concrete	Eco Royal Cement, Eco AR600		
		humid mortar and concrete	Epo Gray P, US Cement, US Cement (less-smelly), US200		
	Notes on Installation	 When you install with divider strips on dried mortar and concrete, recommended adhesives are Eco AR600. Before installation, make sure the arrow marks on the back of each tile, which show the direction of the pattern. For one week after installation, direct sunlight, sudden change of temperature due to air conditioning, and water washing should be avoided. 			
	Recommended Maintenance Wax from TOLI	New FB Wax, U Wax, T Wax (Non-shiny & Antibacterial)			
	Custom Order	If you ask for a different size or thickness, please contact TOLI sales rep.			
	Others	 The dirt and stains will be more visible on the floor covering with lighter plain colors, compared to dark colors. Also they are more likely to stick with the deep-embossed surface than the flat surface. Please be aware that some rubber casters might cause color-contamination. Please note that the product has the indigenous odor from its materials. 			

MV38

MV38





MV29

MV46





MV57

MV37

MV55



vinyl tile / MATICO V





category: vinyl composition tile







▲ MV46/MV60/MV77