



NS4400 AQUATREAD

category: slip-resistant/antibacterial/
heat-resistant vinyl sheet

Slip-resistant vinyl sheet with multiple functions. Its heat-resistance, water-drainage, and durability to dynamic load are most suitable for dry kitchens.

| | | | | | |
|---------------------------------------|--|---|--|----------------|--------------|
| Specification | overall thickness | | 2.0mm | width x length | 1820mm x 20m |
| | others | | Antibacterial Finished / UV-Coated Surface | | |
| JIS Registered No. | No. GB0507188 (JIS A 5705 Vinyl Sheet Flooring) | | | | |
| Packing | 20m/roll | | | | |
| Net Weight | 100.0kg/roll | | | | |
| Recommended Applications | dry kitchens | | | | |
| Recommended Adhesive from TOLI | dried mortar and concrete | Eco Royal Cement, Eco AR600 / (for heavy traffic area) Epo Gray S | | | |
| | humid mortar and concrete | Epo Gray ST, US Cement, US Cement (less-smelly) | | | |
| Welding | Welding rod for heat-welding (antibacterial finished) is available on a color-by-color basis. Seam sealer like TOLI Super Seam Liquid can work as well. Edges should be finished with sealing materials such as TOLI NS Seal. | | | | |
| Notes on Installation | ✦Seams should be heat-welded or finished with a seam sealing bond. ✦When you install 2 different sheets, each edge should be jointed at the seam. (Do not cut in the middle of the sheet.) ✦For one week after installation, direct sunlight, sudden change of temperature due to air conditioning, and water washing should be avoided. ✦Where you can expect the floor will get wet, NS4400 AQUATREAD should be installed in accordance with the method for humid mortar and concrete. Heat-weld or seal the joints, and finish the edges with NS Seal. ✦Please do not use the urethane adhesive other than US Cement, US Cement (less-smelly). | | | | |
| Recommended Maintenance Wax from TOLI | T Wax (Non-shiny & Antibacterial), "HEALTH CARE COAT" from C×S Corporation (Shiny & Antibacterial) | | | | |
| Custom Order | If you ask for higher slip resistance, "NS4400HR" with a harder surface is also available. For more information, please contact TOLI sales rep. | | | | |
| Others | ✦NS4400 AQUA TREAD is for indoor use. Do not install in exterior or semi-exterior places that are exposed to direct sunlight for a long time. ✦In case you install in the areas where you will have oily stains or a lot of water, you might not be able to expect sufficient slip-resistant performance. ✦When you finish the edge with TOLI NS Seal at the high temperature in summer, the bubble might be caused if it's too humid. ✦The dirt and stains will be more visible on the floor covering with lighter plain colors, compared to dark colors. Also they are more likely to stick with the deep-embossed surface than the flat surface. ✦Please be aware that some rubber casters might cause color-contamination. ✦When you apply the finish coating on the top, antibacterial wax should be chosen. Otherwise you cannot expect antibacterial performance. ✦Please note that the product has the indigenous odor from its materials. | | | | |