



GOOD DESIGN



PATCH CORK <GX-4650V>

Patchwork cork bark is well described with a rustic image in silent color tones.

category: carpet tile

Carpet Tile

Composition	surface	BCF Nylon 100%		dyeing method of yarn	Solution Dyed	
	base fabric	Nonwoven Polyester		backing	PVC and Glass Fiber	
Specification	size	250mm×1000mm		overall thickness	9.3mm	
	pile height	H 5.0mm to L 3.0mm (textured loop pile)				
	gauge	1/10	stitch	21.0	yarn weight (oz/sq.yd)	25.7
Packing	12pcs/box = 3m ² /box					
Net Weight	16.5kg/box					
Performance	Critical Radiant Flux	(ASTM E648)	Class 2 Average CRF 0.22/cm ² or higher			
	Smoke Density	(ASTM E662)	Less than 450			
	Flame-retardant	Fire Defense Law in Japan Authorized No.E2190077				
	Antistatic	Less than 1.0kv (JIS L 1021-16, at 23 degrees centigrade, 25%RH)				
	Stain-resistant	Stain Release (NANO CLEAN)				
Formaldehyde Radiation	F☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No. J19-31527					
Way of Installation						
Recommended Adhesive from TOLI	TOLI ECO GA Cement		(required quantity)	for steel or plastic sub-floor	40 to 60 gram/m ²	
				for mortar and wood sub-floor	60 to 100 gram/m ²	
Notes on Installation	<p>◆Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.</p> <p>◆When you install PATCH CORK on the free access floor, each tile should be laid to stride over the joint of free access floor panels in the middle. (The joint of PATCH CORK should not be matched to that of free access floor panels.)</p>					
Others	<p>◆The color shading differs on a tile-by-tile basis. In case you do not feel comfortable about the floor after installation, please change the tiles partly so that it will look natural.</p> <p>◆Please note that the product has the indigenous odor from its materials.</p>					

MADE IN JAPAN



GX4652V



GX4651V



GX4652V



GX4653V

▲ GX4651V/GX4652V/GX4653V/GX4612 (VARIOUS STONE · page 125)/ TTN3214 (LL FREE 50 NW-EX · page 321)

NANO CLEAN

“Nano Clean” provides more excellent stain resistance to soils by adding special Nano finish to the existing stain release by fluoridation.