



## ROCK GARDEN <GX-9250V>

Series of 3-dimentional random stone images will inspire the cobblestone lane. Broad and dynamic floor designs can be created.

category: carpet tile

| Composition   | surface     | BCF                                     | BCF Nylon 100% |                | of yarn Solution Dyed       |  |
|---------------|-------------|---|----------------|----------------|-----------------------------|--|
|               | base fabric | Nonwoven Polyester                      |                | backing        | PVC and Glass Fiber         |  |
| Specification | size        | 250mm×1000mm                            |                | overall thickn | ess 9.3mm                   |  |
|               | pile height | H 8.0mm to L 3.0mm (textured loop pile) |                |                |                             |  |
|               | gauge       | 1/10                                    | stitch         | 14.0           | yarn weight (oz/sq.yd) 20.1 |  |

| Packing                           | $12pcs/box = 3m^2/box$  |   |  |                               |  |  |  |
|-----------------------------------|---|---|--|-------------------------------|--|--|--|
| Net Weight                        | 17.0kg/box  |   |  |                               |  |  |  |
| Performance                       | Critical Radiant Flux   | (ASTM E648) Class   | (ASTM E648) Class 2 Average CRF 0.22/cm² or higher |                               |  |  |  |
|                                   | Smoke Density   | (ASTM E662) Less than 450   |  |                               |  |  |  |
|                                   | Flame-retardant   | lame-retardant Fire Defense Law in Japan Authorized No.E2180254           |  |                               |  |  |  |
|                                   | Antistatic  | tistatic Less than 1.0kv (JIS L 1021-16, at 23 degrees centigrade, 25%RH) |  |                               |  |  |  |
|                                   | Stain-resistant Stain Release   |   |  |                               |  |  |  |
|                                   | Formaldehyde Radiation  | F <sup>™</sup> ☆☆☆☆ Interior-fabrics Per                                  | formance Evaluation Conference                     | Certified No. J18-21150       |  |  |  |
| Way of Installation               | Î ↑ Î↑ Ashlar or ↑↑↑↑ Monolithic  |   |  |                               |  |  |  |
| Recommended<br>Adhesive from TOLI | TOLI ECO GA Cement  | (required quantity) ———   | for steel or plastic sub-floor                     | 40 to 60 gram/m <sup>2</sup>  |  |  |  |
| Adilesive Holli Tolli             |   |   | or mortar and wood sub-floor                       | 60 to 100 gram/m <sup>2</sup> |  |  |  |
| Notes on Installation             | <ul> <li>◆Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.</li> <li>◆When you install ROCK GARDEN on the free access floor, each tile should be laid to stride over the joint of free access floor panels in the middle. (The joint of ROCK GARDEN should not be matched to that of free access floor panels.)</li> </ul> |   |  |                               |  |  |  |
| Others                            | <ul> <li>◆The color shading differs on a tile-by-tile basis. In case you do not feel comfortable about the floor after installation, please change the tiles partly so that it will look natural.</li> <li>◆Please note that the product has the indigenous odor from its materials.</li> </ul>   |   |  |                               |  |  |  |

MADE IN JAPAN



 $\blacktriangle \ \ GX9251V/GX9252V/GX4212 \ \ (PRARIE \cdot page \ 126)$ 





GX9251V



**GX9252V** 



|| GX9253V