



YUTAKA2000 < YU-2200 > NATURE CRESCENDO

(made-to-order product)


category: carpet tile

Vibrant gradation inspired by expressive nature. Beautiful colors symbolizing ocean, forest, and ground will stand out more in spacious areas.

Composition	surface	BCF Nylon 100% (type 6)	dyeing method of yarn	Piece Dyed
	base fabric	Nonwoven Polyester	backing	PVC and Glass Fiber
Specification	size	500mm×500mm	overall thickness	7.3mm
	pile height	H 5.0mm / L 3.5mm (textured loop pile)		
	gauge	1/10	stitch	11.2

Packing	$16pcs/box = 4m^2/box$					
Net Weight	21.0kg/box					
Performance	Critical Radiant Flux	ritical Radiant Flux (ASTM E648) Class 1 Average CRF 0.45/cm² or higher		ner		
	Smoke Density	(ASTM E662)	Less than 450			
	Flame-retardant	Fire Defense Law in Japan Authorized No.E2150287				
	Antistatic	0.05kV (AATCC 134)				
	Stain-resistant		Stain Release (Antifouling Finished)			
Way of Installation	↑ ↑ ↑ Monolithic or					
Recommended Adhesive from TOLI	TOUL FOO CA Commont	(ve assisted assembles)	for steel or plastic sub-floor	40 to 60 gram/m ²		
	TOLI ECO GA Cement	(required quantity)	for mortar and wood sub-floor	60 to 100 gram/m ²		
Notes on Installation	Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.					
Others	The stripes differ in position on a tile-by-tile basis so that they will not be exactly connected between the tiles (please refer to the installation image).					

MADE IN JAPAN

















|| YU2225 || YU2226