







**GA-100T** Soft-textured lattice pattern. With its beautiful crisscross shading, classy (SOFT GRID) atmosphere can be created in your space.
GOOD DESIGN LONG LIFE DESIGN AWARDwinning product in 2015.

Composition	surface	BCF	Nylon 100%	dyeing method	of yarn Piece Dy	Piece Dyed	
	base fabric	Nonwo	oven Polyester	backing	PVC and Glas	PVC and Glass Fiber	
Specification	size	500n	nm×500mm	overall thickn	ess 7.8mn	7.8mm	
	pile height	5.0 to 3.0mm (textured loop pile)					
	gauge	1/10	stitch	14.0	yarn weight (oz/sq.yd)	17.1	

	gauge 1/10	Stitcii	14.0	yarri weight (02/ 3q.yu)	11.1			
Packing	$20pcs/box = 5m^2/box$							
Net Weight	24.0kg/box							
Performance	Critical Radiant Flux	(ASTM E648) Class 2 Average CRF 0.22/cm² or higher						
	Smoke Density	(ASTM E662) Less than 450						
	Flame-retardant	Fire Defense Law in Japan Authorized No.E2170234						
	Antistatic	Less than 1.0kV (JIS L 1021-16, at 23 degrees centigrade, 25%RH)						
	Stain-resistant	Stain Release						
	Formaldehyde Radiation	F "☆☆☆☆ Interior-fabri	cs Performance Evaluat	ion Conference Certified No.J1	7-31267			
Way of Installation	↑ ↑ ↑ Monolithic or ↑ ↑ Quarter Turn							
Recommended Adhesive from TOLI	TOU 500 04 0	(	for steel or plastic	sub-floor 40 to 60 gi	ram/m²			
	TOLI ECO GA Cement	(required quantity)	for mortar and woo	d sub-floor 60 to 100 g	ram/m²			
Notes on Installation	◆Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly.							
Others	<ul> <li>♦In Monolithic installation, when the color difference between the tiles stands out or the joints are visible, please switch the tiles partly.</li> <li>♦Please note that the product has the indigenous odor from its materials.</li> <li>♦Right after installation, color shading could be seen on the floor. This is just because surface piles partially lie down. With the passage of time, it will disappear.</li> <li>♦The linear pattern may not be strictly straight, which is the characteristic of this particular product with a fabric image.</li> </ul>							
Custom Order	All the standard colors of GA-100T can be made with Nano Clean finish (patent-obtained special stain release) on a made-to-order basis. For more information, please contact TOLI sales reps.							

MADE IN JAPAN

GA10635T



|| GA10632T



**GA10633T** 

GA10634T



GA10635T



|| GA10636T





▲ GA10632T

