

GA-400RSThe sister product of GA-400 with unique random stripe images, which will broaden your color coordination.

Composition	surface	Polypropylene 100%		dyeing method o	f yarn Solution Dyed
	base fabric	Nonwoven Polyester		backing	PVC and Glass Fiber
Specification	size	500mm×500mm		overall thickne	ess 6.0mm
	pile height	3.0mm (loop pile)			
	gauge	1/10	stitch	14.0	yarn weight (oz/sq.yd) 16.5

Packing	$20pcs/box = 5m^2/box$				
Net Weight	22.0kg/box				
Performance	Smoke Density	(ASTM E662)	Less than 450		
	Flame-retardant	Fire Defense Law in Japan Authorized No.E0970014			
	Antistatic	Less than 1.0kV (JIS L 1021-16, at 23 degrees centigrade, 25%RH)			
	Formaldehyde Radiation	F [™] ☆☆☆☆ Interior-fabric	rics Performance Evaluation Conference Certified No. J06-30		
Way of Installation	Quarter Turn				
Recommended	TOULECO CA Comont	(required quantity)	for steel or plastic sub-floor	40 to 60 gram/m ²	
Adhesive from TOLI	Adhesive from TOLI TOLI ECO GA Cement (require	(required quantity) -	for mortar and wood sub-floor	60 to 100 gram/m ²	
Notes on Installation	+Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translucent, install the tiles. Be careful not to put the tiles too tightly. ◆The design differs on a tile-by-tile basis. After installation, in case you feel uncomfortable about the floor image, switch the tiles partially so that it will have a natural at-random image.				
Others	Please note that the product has the indigenous odor from its materials.				

MADE IN JAPAN

GA4501R



GA4501R



GA4505R





|| GA4601R



|| GA4605R

GA-400RS can be coordinated with GA-400.

GA4501R	GA4001 (page 78)	GA4003 (page 78)					
GA45UIR	GA4004 (page 78)	GA4007 (page 78)					
GA4505R	GA4005 (page 78)	GA4007 (page 78)					
GA4505R	GA4032 (page 78)	GA4035 (page 78)					
GA4601R	GA4001 (page 78)	GA4004 (page 78)					
GA4605R	GA4005 (page 78)	GA4032 (page 78)					



▲ GA4601R/GA4004 (GA-400 · page 78)