

# GA-400N

category: carpet tile

GA-400's sister product which has a pre-applied adhesive on the back.

Easy to install and very much suitable for free access floor panels.

Composition	surface	Polypropylene 100%		dyeing method of yarn		Solution Dyed	
	base fabric	Nonwoven Polyester		backing		PVC and Glass Fiber	
Specification	size	500mm×500mm		overall thickness		6.0mm	
	pile height	3.0mm (loop pile)					
	gauge	1/10	stitch	14.0	yarn weight (oz/sq.yd)	16.5	
Packing	20pcs/box = 5m <sup>2</sup> /box						
Net Weight	22.0kg/box						
Performance	Flame-retardant	Fire Defense Law in Japan Authorized No.E0080104					
	Antistatic	Less than 1.0kV (JIS L 1021-16, at 23 degrees centigrade, 25%RH)					
	Formaldehyde Radiation	F☆☆☆☆ Interior-fabrics Performance Evaluation Conference Certified No.J08-30531					
Way of Installation	<div><div><div>↑</div><div>→</div><div>→</div><div>↑</div></div>Quarter Turn</div>						
Notes on Installation	♦GA-400N is very much suitable for free access floor panel made of metal or resin. However, in case the panel surface is apparently bumpy, GA-400N cannot be tightly stuck. Also, some resins are not exactly compatible with GA-400N's pre-applied adhesive (e.g. polypropylene), so that the adhesion might be weaker. ♦For GAN4405S, due to striped designs, the crossover point of joints may appear to be misaligned. This is optional illusion, not a manufacturing defect. ♦You can install GA-400N on the existing vinyl sheet or tile with the flat surface. If you need to remove them again, apply the wax sufficiently on the vinyl floor surface before installation. ♦Do not install GA-400N where you can expect heavy casters will frequently come and go. ♦Do not install GA-400N on dusty sub-floors such as mortar, nor elastic sub-floors like radiant-heating floors.						
Others	Please note that the product has the indigenous odor from its materials.						

MADE IN JAPAN



GAN4009



GAN4001



GAN4004



GAN4009



GAN4405S

## Sub-Floor Application Table



sub-floor		Applicable or Not Applicable
Access Flooring	metallic surface or plastic surface	OK
	concrete	N/A
Vinyl Tile & Vinyl Sheet		OK
Stone		OK
Linoleum		N/A
Mortar		N/A
Particle Board		N/A
Needle Punch Carpet		N/A
Floor Heating Panel		N/A
Wood Flooring		Could be discolored or changed in quality

The floor covering may be less sticky if used on extremely uneven ground or polypropylene resin.