

New seam finish designed for TOLI NW series (vinyl sheet),
which surpasses existing heat-welding.

TOLI JOINT SHIELD

Available for TOLI NW
series (vinyl sheet):

- FLOORLEUM NW SERIES
- DEODORANT NS TOWARE NW
- NONWAXLEUM NW
- SF FLOOR NW
- CARE SAFE NW
- HOSPILEUM NW
- MATURE NW
- HITOE GRANZA/HITOE FINE



Vinyl
Sheet



Seam joints are least visible.

The seam joints of a vinyl
sheet are least visible. This is
why the floor image will not
be split apart by the joints.



Assured strength and durability

Strength and
durability are as good
as welding rods.



Simple installation

Simple and
easy-to-follow installation
by taking 4 steps.



POINT

1 Seam joints are least visible.



POINT

2 Strength and durability are as good as welding rods.

test item	TOLI JOINT SHIELD	welding rod	evaluation
floor covering	HOSPILEUM NW		—
strength	110N~130N		TOLI JOINT SHIELD has the same strength as welding rod.
durability	Nothing abnormal detected after 180 minutes passed.		The required endurance time to dynamic loads is 180 minutes. Therefore this result can be judged as sufficiently durable.

POINT

3 Simple installation by taking 4 steps.

※For more information about the installation, please contact TOLI sales rep.



product name	TOLI JOINT SHIELD full set	TOLI JOINT SHIELD liquid set	spare nozzle set
description	"All-in-one" package for JOINT SHIELD Method which has a full set of required tools.	The package for JOINT SHIELD Method which has all the required tools except the nozzles.	10 spare nozzles for JOINT SHIELD Method.
product category	seam finish material for floor covering		—
method	JOINT SHIELD Method		—
image			
specification & contents	180g/set [liquid, bottle, tape, installation guide, sponge, and nozzle]	180g/set [liquid, bottle, tape, installation guide, and sponge]	10 spare nozzles
standard qty	50m/set	50m/set	—
number of colors	9 colors ○ ● ● ● ● ● ● ● ● ●		
color code	FL/NS/TS/SF/FS/HTE/CAR + JS + color number for the selected vinyl sheet + FU e.g. FSJS2001FU	FL/NS/TS/SF/FS/HTE/CAR + JS + color number for the selected vinyl sheet + EK e.g. FSJS2001EK	JSHARI

※TOLI JOINT SHIELD can also work on the top of TOLI UNDERLAY SHEET, but when partial weight will be put on the floor (such as heavy stuff or casters), the seam joints should not be finished with TOLI JOINT SHIELD.