

CO2-




category: carpet tile

Charcoal based modular tiles with urbane taste. Vivid pinstripes will lend brilliance to the floor.

Composition	surface	BCF Nylon 100%	dyeing method of yarn	Solution Dyed
	base fabric	Nonwoven Polyester	backing	PVC and Glass Fiber
Specification	size	500mm x 500mm	overall thickness	6.5mm
	pile height	3.0mm (loop pile)		
	gauge	1/10	stitch	13.5
Packing	16pcs/box = 4m ² /box			
Net Weight	19.2kg/box			
Performance	Critical Radiant Flux	(ASTM E648) 0	lass 1 Average CRF 0.45/cm ² or high	er
	Smoke Density	(ASTM E662)	Less than 450	
	Flame-retardant	Fire Defense Law in Japan Authorized No.E2120131		
	Antistatic	Less than 1.0kv (JIS L 1021-16, at 23 degrees certigrate, 25% RH)		
	Stain-resistant		Stain Release	
Way of Installation	↓ → Quarter Turn			
Recommended Adhesive from TOLI	TOLI ECO GA Cement	(required quantity) -	for steel or plastic sub-floor	40 to 60 gram/m ²
			for mortar and wood sub-floor	60 to 100 gram/m ²
Notes on Installation	Apply the adhesive on the whole surface of the sub-floor thinly and evenly. After drying, when the adhesive becomes translu- cent, install the tiles. Be careful not to put the tiles too tightly.			
Others	 Due to striped designs, the crossover point of joints may appear to be misaligned. This is an optical illusion, not a manufacturing defect. Please note that the product has the indigenous odor from its materials. When you store the products, do not pile up more than 6 boxes for a better preservation. 			

MADE IN JAPAN





YU1307



YU1310



VU1308



VU1311



YU1309



VU1312





Carpet Tile



▲ YU1307/YU1309

